



## **L301 Color Label Printer**

### Ideal for Small Businesses

Creating professional labels on demand is easy with the L301. Bringing short-run label printing in-house saves time and money. Eliminate lead times, setup fees, plate changing fees and the minimum order quantites associated with outsourcing labels.

The L301's roll printing capability allows businesses to print professional quality labels as needed. No more wasted time, wasted money, or wasted labels.

### KeyFeatures

- ✓ Professional looking labels, on demand
- ✓ Simplify workflows and eliminate the hassles of sheet printing.
- ✓ Flexibility to change label designs and content on the fly
- ✓ Minimise waste by printing only the labels you need
- ✓ Economically priced specically for small businesses







# L301 Specifications

#### General:

Black Mark Size:

Label Thickness:
Manual Cutter:

Manual Unwinder:

Print Technology: **HP Thermal Inkjet Print Resolutions:** Color: Up to 4800 x 1200 optimized dpi color; Black: Up to 1200 x 1200 rendered dpi Print Speed: Approximately 1.8 in/sec (46mm/sec) when printing a 2.2 inch wide (56mm) image in draft mode Size: 19"w x 21.5"d x 7"h (48.3cm x 54.6cm x 17.8cm) Inks: Black single pigment ink cartridge; Tri-color single dye ink cartridge Compatible with wide range of paper, polyester, polypropylene, and vinyl label stocks. Media Types: Supports gap, black mark, and continuous media Media Sensing: Auto calibration and auto detection of gap and black marks Minimum Label Size: 2"w x 1"h (51mm x 25mm) 6"w\* x 48"h (152mm\* x 1219mm) Maximum Label Size: - \*Up to 8.5 "w (216mm) with optional powered unwinder Inter Label Gap Size: 0.125" - 0.3" (3mm x 8mm)

## Operating Environment:

0.125" - 0.3"

Included

0.004" - 0.01"(0.1mm - 0.3mm)

Included, 6" max width, 6" OD (152mm)

Display: Front panel touch screen Operating Systems: Windows 7, 8, and 10 (32 and 64 bit) Data Interface: USB 2.0 connection Operating Temperature: 41 - 104°F (5 - 40℃) Storage Temperature: -40 − 140° F (-40 − 60°C) Operating Humidity: 15 - 80% RH. 20 - 80% recommended Non-operating Humidity: 10 - 90%1-year Warranty:



Label Printing Solutions for Every Level of Production
Afinialabel.co.uk

